




## Strain relief type ZL-fix



### Product information

The strain relief ZL-fix may be used wherever cables, cords, wires or conduits must be relieved or routed in a way that is secure, easy and cost-effective. The strain relief ZL-fix is available in two versions, either for direct screw fastening (flat-head screw M5, not included in delivery) or for fastening on a profile with 10 mm groove width (integrated nut strap).

- Do not constrict sensitive cables such as fibre optic cables or pneumatic hoses
- No-tools fastening hook-and-loop system can be opened and closed infinitely
- Very simple handling
- Variable installation positions

PU pcs.: 10


### Information, conformities and approvals



Article	Order No.	Length of hook-and-loop tape mm	Section groove min. - max. mm
<b>Profile assembly</b>			
ZL-fix P-15	87705018	92	9.9 - 10.8
ZL-fix P-25	87705020	171	9.9 - 10.8
ZL-fix P8-25	87705030	170	7.9 - 8.8
ZL-fix P-35	87705022	171	9.9 - 10.8
<b>Screw assembly</b>			
ZL-fix W-15	87705008	92	
ZL-fix W-25	87705010	171	
ZL-fix W-25-400	87705015	400	
ZL-fix W-35	87705012	171	



## Strain relief type ZL-fix



### Strain relief

B mm: 34  
EH mm: 10.7  
Ø mm: 5

Article	Order No.	A mm	M mm
<b>Profile assembly</b>			
ZL-fix P-15	87705018	30	15
ZL-fix P-25	87705020	37	25
ZL-fix P8-25	87705030	25	
ZL-fix P-35	87705022	45	35
<b>Screw assembly</b>			
ZL-fix W-15	87705008	39	15
ZL-fix W-25	87705010	37	25
ZL-fix W-25-400	87705015	37	25
ZL-fix W-35	87705012	45	35



## Strain relief type ZL-fix

### Material properties



Coated polyamidePolyamide 6.6

### Thermal properties



Temperature / temperature range -30 °C – 80 °C

### Technical information



Halogen-free



LABS free



According to EN -2-1

### Conformity



RoHS (EC Directive 2011/65/EU)

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.