

ABB IRB 4600



Product information

Our tailor-made empty pipe packages offer the ideal solution for your robot.

Your advantages at a glance:

- \bullet Individual adjustment: The corrugated tube can be shortened if necessary to ensure a perfect fit.
- Fast delivery time: Benefit from a fast delivery time for your complete solutions.
- Easy installation: Quick and easy assembly saves valuable time.
- Flexible strain relief: Our hose packages contain two adjustable cable star blanks for optimal strain relief and termination. If required, we offer water jet machining.
- Longevity: Robust materials ensure a long service life and less maintenance.
- \bullet Optimal protection: Protect your cables from wear and external influences. Our products ensure worry-free operation.
- Everything from a single source: Get individual products, complete solutions, service and advice from a single source.

Information, conformities and approvals







Article	Order No.	Corrugated conduit	Corrugated conduit size	Condition	Diameter	Diameter	Retraction system	Spring strength	Axis	Strain relief strength	PU
					inside	outside				•	pcs.
IRB 4600	MS82501000000680	EWX-PAE	M40/P36	Closed	28.5	42.2	R-Tec Box	80	A3-A6	Cable star	1
IRB 4600	MS82501000000681	EWX-PAE	M50/P48	Closed	36.7	53.5	R-Tec Box	100	A3-A6	Cable star	1
IRB 4600	MS82501000000683	EWX-PAE	NW 56	Closed	52.2	67.7	R-Tec Box	200	A3-A6	Cable star	1
IRB 4600	MS82501000000684	EWX-PAE	NW 70	Closed	64	80.3	R-Tec Box	200	A3-A6	Cable star	1

Material properties



mod. polyamide PA 12 mod. polyamide PA 6 Thermoplastic elastomer Steel, powder coated

Thermal properties



Temperature / temperature range

–40 °C – 110 °C / short term: 140 °C

© Murrplastik Systemtechnik GmbH • 1 as of 2025-05-13 - 257280



ABB IRB 4600

Chemical resistances



Resistant to:

Alcohol Greases Lyes Mineral oils Weak acids

Technical information



Halogen-free