


Type MWKM (metal version with multi-insert)





Product information

The MWKM is a metal cable fitting made of nickel-plated brass, specially modified polyamide and an additional multi-insert that makes it possible to run multiple cables through a cable fitting.

The MWKM cable fittings feature the following advantages:

- Integrated multi-insert
- High tightness
- · Easy to assemble
- Type OR O-ring included in delivery

Color: Silver

Information, conformities and approvals







Article	Order No.	Connecting thread	EH mm	GL mm	No. Openings	Diameter mm	SW 1 / 2 mm	PU pcs.
MWKM-Pg 09-2x3 ¹⁾	84121810	PG 09	21	6	2	3	17 / 17	50
MWKM-Pg 09-4x1.41)	84121812	PG 09	21	6	4	1.4	17 / 17	50
MWKM-Pg 11-2x3 ¹⁾	84121814	PG 11	22	6	2	3	20 / 20	50
MWKM-Pg 11-2x4 ¹⁾	84121816	PG 11	22	6	2	4	20 / 20	50
MWKM-Pg 11-3x3 ¹⁾	84121818	PG 11	22	6	3	3	20 / 20	50
MWKM-Pg 13.5-2x5 ²⁾	84121820	PG 13,5	24	6.5	2	5	22 / 22	50
MWKM-Pg 13.5-3x2 ¹⁾	84121822	PG 13,5	24	6.5	3	2	22 / 22	50
MWKM-Pg 13.5-3x4 ¹⁾	84121824	PG 13,5	24	6.5	3	4	22 / 22	50
MWKM-Pg 13.5-6x3 ¹⁾	84121826	PG 13,5	22	6.5	6	3	22 / 22	50
MWKM-Pg 16-2x6 ²⁾	84121828	PG 16	23	6.5	2	6	24 / 24	50
MWKM-Pg 16-3x3 ¹⁾	84121830	PG 16	23	6.5	3	3	24 / 24	50



Type MWKM (metal version with multi-insert)

Article	Order No.	Connecting thread	EH mm	GL mm	No. Openings	Diameter mm	SW 1 / 2 mm	PU pcs.
MWKM-Pg 16-3x4 ¹⁾	84121832	PG 16	23	6.5	3	3	24 / 24	50
MWKM-Pg 16-3x6 ¹⁾	84121834	PG 16	23	6.5	3	6	24 / 24	50
MWKM-Pg 16-4x4 ¹⁾	84121836	PG 16	23	6.5	4	4	24 / 24	50
MWKM-Pg 16-5x4 ²⁾	84121838	PG 16	23	6.5	5	4	24 / 24	50
MWKM-Pg 16-6x4 ¹⁾	84121840	PG 16	23	6.5	6	4	24 / 24	50
MWKM-Pg 21-2x8 ¹⁾	84121842	PG 21	24	7	2	8	30 / 30	25
MWKM-Pg 21-3x7 ¹⁾	84121844	PG 21	24	7	3	7	30 / 30	25
MWKM-Pg 21-4x6 1)	84121846	PG 21	24	7	4	6	30 / 30	25

¹⁾ With cURus- approval

²⁾ Discontinued product!

Material properties



Brass nickel-platedmod. polyamide PA 6

Thermal properties



Temperature / temperature range -40 °C – 100 °C short termshort term: 120 °C

Protection class



Protection class IP65, IP68 with optimum configuration and with additional O-ring, type OR

Conformity



RoHS (EC Directive 2011/65/EU)

Approvals and operating permits



CSA approval

CURLS approval given in our safet Microfuses and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.