


Klemsan®

End Sleeves

Insulated Type




Insulated type of end sleeves are made of E-Cu with tin-plating. (DIN 46228/4) The material of the insulation parts polyamide 6.6.

Type	Cat. No.	Cross-Sec. (mm ²)	L (mm)	Color	AWG	Qty.
IKY 0,5/8	570 010	0,50	14	Orange	20	500
IKY 0,75/8	570 020	0,75	14	White	18	500
IKY 1,0/8	570 030	1,0	14	Yellow	17	500
IKY 1,5/8	570 040	1,5	14	Red	16	500
IKY 2,5/8	570 050	2,5	15	Blue	14	250
IKY 4/9	570 060	4	16	Grey	12	250
IKY 6/12	570 070	6	20	Black	10	100
IKY 10/12	570 080	10	21	Ivory	8	100
IKY 16/12	570 090	16	22	Green	6	50
IKY 25/16	570 100	25	29	Brown	4	20
IKY 35/16	570 110	35	30	Beige	2	20
IKY 50/20	570 120	50	36	Olive	1	20



Uninsulated Type



Uninsulated end sleeves are made of E-Cu with tin-plating as per DIN 46228/1.

Type	Cat. No.	Cross-Sec. (mm ²)	L (mm)	AWG	Qty.
KY 0,50/10	571 010	0,50	10	20	1000
KY 0,75/10	571 020	0,75	10	18	1000
KY 1,0/10	571 030	1,0	10	17	1000
KY 1,5/10	571 040	1,5	10	16	1000
KY 2,5/12	571 050	2,5	12	14	1000
KY 4,0/12	571 060	4,0	12	12	500
KY 6,0/12	571 070	6,0	12	10	250
KY 10,0/12	571 080	10,0	12	8	250
KY 16,0/12	571 090	16,0	12	6	100



Twin Cord end Terminals



Insulated twin cord end sleeves are made of E-Cu with tin-plating as per DIN 46228/4.

Type	Cat. No.	Cross-Sec. (mm ²)	Color	Qty.
IKY - 2 x 0,5/8	572 010	2 x 0,5	Orange	500
IKY - 2 x 0,75/8	572 020	2 x 0,75	White	500
IKY - 2 x 1/8	572 030	2 x 1,0	Yellow	500
IKY - 2 x 1,5/8	572 040	2 x 1,5	Red	250
IKY - 2 x 2,5/10	572 050	2 x 2,5	Blue	200
IKY - 2 x 4/12	572 060	2 x 4,0	Grey	100
IKY - 2 x 6/14	572 070	2 x 6,0	Black	75
IKY - 2 x 10/14	572 080	2 x 10	Ivory	50
IKY - 2 x 16/14	572 090	2 x 16	Green	20