

Klemsan®

670300 PANO PRIZI UPS

Din rail socket (UPS)



General Product Information

Cross-Section	6
Current	16 V
Depth (mm)	46.70 mm
Height (mm)	74.80 mm
Voltage	250 V
Width (mm)	41.80 mm
Min.-Max. Single and Fine Strand (mm ²)	0.5-10.0 mm ²
Conductors with ferrules (mm ²)	0.5-6.0 mm ²

Order Info

670300 Din rail socket (UPS)

© 2019 Klemsan A.Ş.
www.klemsan.com

DIN Rail Sockets

PAP



PAP - LED



	DIN Rail Socket Earth	DIN Rail Socket LED + Earth
Cat. No.	670 100	670 200
Qty.	1	1
Width / Height / Depth (mm)	41.80 / 74.80 / 49.20	41.80 / 74.80 / 49.20
Voltage / Current / Cross-Section	250 V / 16 A / 6 mm ²	250 V / 16 A / 6 mm ²
Single ve Fine Strand, (mm ²)	0.5 - 10	0.5 - 10
Conductors with ferrules (mm ²)	0.5 - 6	0.5 - 6

PAP - UPS



PAP - UPS + LED



PAP - KK



DIN Rail Socket UPS	DIN Rail Socket LED + UPS	DIN Rail Socket Children Protection + Earth
670 300	670 400	670 500
1	1	1
41.80 / 74.80 / 46.70	41.80 / 74.80 / 46.70	41.80 / 74.80 / 46.70
250 V / 16 A / 6 mm ²	250 V / 16 A / 6 mm ²	250 V / 16 A / 6 mm ²
0.5 - 10	0.5 - 10	0.5 - 10
0.5 - 6	0.5 - 6	0.5 - 6