


ORTAC METAL LOCK NUTS SERIES

Following characteristics;

- High heat and impact resistance
- Brass, nickel plated
- Connection thread norms (DIN 40430 / EN 60423)
- Mostly used in every units of brass PG & Metric threads assembling

METAL LOCK NUTS BRASS




PİRİNÇ SOMUN

- Hammaddesi : Pirinç, nikel kaplı
Bağlantı dişi M : EN 60423
Bağlantı dişi PG : DIN 40430

METRIC/PG THREAD LOCK NUTS

PRODUCT RANGE OVERVIEW

AG Thread	Code	H mm	 mm
M 12 x 1,5	OMBL 01	2,8	15
M 16 x 1,5	OMBL 02	3	19
M 20 x 1,5	OMBL 03	3,5	24
M 25 x 1,5	OMBL 04	3,5	30
M 32 x 1,5	OMBL 05	4	36
M 40 x 1,5	OMBL 06	4	45
M 50 x 1,5	OMBL 07	5	55
M 63 x 1,5	OMBL 08	5	68
PG 7	OPBL 01	2,8	15
PG 9	OPBL 02	2,8	18
PG 11	OPBL 03	3	21
PG 13,5	OPBL 04	3	23
PG 16	OPBL 05	3	26
PG 21	OPBL 06	3,5	32
PG 29	OPBL 07	4	40
PG 36	OPBL 08	5	50
PG 42	OPBL 09	5	60
PG 48	OPBL 10	5,5	64