



Klemsan®

420020 PSK 1/2

General Product Information	Insulating material	—
	Inflammability class acc. to UL 94	—
	Packing Unit	—
	Weight (g)	—
TSE / CE Technical Data	Nominal Voltage	400 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm ²
	Norm	EN 60998-2-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5 mm ²
	VDE Norm	IEC 60998-1/IEC 60998-2-1
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5
Connection Data	Minimum solid strand cross section	— mm ²
	Maximum solid Strand cross section	— mm ²
	Minimum fine Strand cross section	— mm ²
	Maximum fine strand cross section	— mm ²
	AWG Conductor Range	—
	Connection Type	screw/vidal
	Insulation Stripping length	5 mm
	Tightening torque	0.4/0.6 Nm

Türk Standartlarına Uygunluk Belgesi - TSE Certificate

Avrupa standartlarına uygunluk belgesi - CE Certificate

LAPEM - RETIE Sertifikası - LAPEM - Retie Certificate

Order Info

420020

© 2019 Klemsan A.Ş.
www.klemsan.com

Terminals Strips


- The product in the figure is the new psk 1/2 terminal strip.
- For allowing marking, label slots are designed according to DB 5 and DG 6/5 Marking Tags (Dekafix)
- Assembly of the terminal should be made with maximum 3 mm Width screw.




PSK 1/2
420 020



PSK 2/2
421 020



PSK 2/10
421 100



Electrical Ratings	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section
TSE (EN 60998-2-1)	400 V ~ / 24 A / 2,5 mm ²	660 V ~ / 41 A / 6 mm ²	660 V ~ / 41 A / 6 mm ²
Insulation Stripping Length (min.-max.)	5 mm	9 mm	9 mm
Torque	0,4 - 0,6 Nm	0,5 - 0,8 Nm	0,5 - 0,8 Nm
Qty.			
	100	100	20
Screwdriver			
	IKT3 (0,6x3,5)		