



**Natural** : Made from U.L. approved polyamide 66.  
Flammability rating : UL 94 V-2  
Normal service temperature range : - 40° C to 85° C.

**Black** : Material and temperature as above, except in black color.  
Specification : Made to comply with mil-spec drawing no. MS-3667  
tensile strength meet or exceed MIL-S-23190 D standart.

Type	Cat. No.	Width (mm)	Length (mm)	Max. Bundle Dia. (mm)	Max. Tensite Strength (KGs)	Qty.
YKB 94	<b>532 094 B</b>	2,5	94	25	8	1000
YKB 94	<b>532 094 S</b>	2,5	94	25	8	1000
YKB 100	<b>532 100 B</b>	2,5	100	25	8	1000
YKB 100	<b>532 100 S</b>	2,5	100	25	8	1000
YKB 142	<b>532 142 B</b>	2,5	142	35	8	1000
YKB 142	<b>532 142 S</b>	2,5	142	35	8	1000
YKB 203	<b>532 203 B</b>	2,5	203	55	8	1000
YKB 203	<b>532 203 S</b>	2,5	203	55	8	1000
YKB 150	<b>533 150 B</b>	3,6	150	39	18	1000
YKB 150	<b>533 150 S</b>	3,6	150	39	18	1000
YKB 250	<b>533 250 B</b>	3,6	250	74	18	1000
YKB 250	<b>533 250 S</b>	3,6	250	74	18	1000
YKB 292	<b>533 292 B</b>	3,6	292	85	18	1000
YKB 292	<b>533 292 S</b>	3,6	292	85	18	1000
YKB 368	<b>533 368 B</b>	3,6	368	102	18	1000
YKB 368	<b>533 368 S</b>	3,6	368	102	18	1000
YKB 120	<b>534 120 B</b>	4,8	120	30	22	1000
YKB 120	<b>534 120 S</b>	4,8	120	30	22	1000
YKB 190	<b>534 190 B</b>	4,8	190	52	22	1000
YKB 190	<b>534 190 S</b>	4,8	190	52	22	1000
YKB 368	<b>534 368 B</b>	4,8	368	102	22	1000
YKB 368	<b>534 368 S</b>	4,8	368	102	22	1000
YKB 300	<b>537 300 B</b>	7,6	300	88	55	500
YKB 300	<b>537 300 S</b>	7,6	300	88	55	500
YKB 380	<b>537 380 B</b>	7,6	380	110	55	500
YKB 380	<b>537 380 S</b>	7,6	380	110	55	500
YKB 450	<b>538 450 B</b>	8,0	450	133	80	1000
YKB 450	<b>538 450 S</b>	8,0	450	133	80	1000
YKB 762	<b>539 762 B</b>	9,0	762	236	80	1000
YKB 762	<b>539 762 S</b>	9,0	762	236	80	1000

B or S codes at the end of each cat. number indicate the color of the cable-tie. Please contact for any requirements apart from the list.

B : Natural, White  
S : Black